

## FEATURES & BENEFITS

- ▶ #6600-01 Tilting Reflector with 60 mm diameter reflective material, range up to 150 m (492 ft), mounts to Swiss-style Quick Release Adapters, adjustable on two axes, made of yellow Delrin® material
- ▶ #6600-03 Tilting Reflector with Printed Cross Hair is the same as #6600-01 but with a printed cross-hair target on both sides
- ▶ #6600-04 is similar to the #6600-01 but with a 25 mm Mini Prism for ranges up to 2,000 ft (600 m) or more with most instruments
- ▶ #6600-02 Mini 'L' Bar Prism features a copper-coated prism, is for longer range applications, up to 2,000 ft (600 m) with most instruments, anodized aluminum construction, comes with a 10.3 mm (0.40 inch) mounting hole
- ▶ #6600-05 Mini 'L' Bar Prism is the same as the #6600-02 but has a silver-coated prism that is permanently bonded to the holder making it water and dust proof

## APPLICATIONS

- ▶ Mining, tunneling, monitoring and rail



[www.surveying.com](http://www.surveying.com)

# Lightweight and Inexpensive; Designed to Be Set-Up and Left

### 6600-Series Tilting Reflectors and 'L' Bar Mini Prisms



#6600-01



#6600-03



#6600-04



#6600-02



#6600-05

PART NO.	PRISM OFFSET	DIAMETER
6600-01	2 mm	60 mm Reflective Material
6600-02	-25 mm	25 mm Copper-Coated Mini Prism
6600-03	2 mm	60 mm Reflective Material
6600-04	-17.5 mm	25 mm Mini Prism
6600-05	-25 mm	25 mm Silver-Coated Mini Prism

Contact your local SECO dealer today!

## FEATURES & BENEFITS

- ▶ #6601-Series Quick Release Adapters are made of T-303 stainless steel with machined threads that attach to corresponding Anchor Bolts or the #6602-Series rebar bolts
- ▶ #5187-00 Quick Release Adapter with female 5/8 x 11 threads, made of anodized aluminum
- ▶ #6602-Series Rebar Bolts measures 3/4 x 9.9 in (19.05 x 251.46 mm) long and comes with a hex bolt used to hammer the bolt in the surface, remove the hex bolt and install the #6601-Series Adapter
- ▶ Reflector targets and adapters can be easily removed when no longer needed

## APPLICATIONS

- ▶ Mining, tunneling, monitoring and rail



[www.surveying.com](http://www.surveying.com)

# Lightweight and Inexpensive; Designed to Be Set-Up and Left

6601 and 6602 Quick Release Adapters and Rebar Bolts



#6601-01



#6601-02



#6601-03



#6601-04



#6602-01



#6602-02



#5187-00

PART NO.	THREADS	WEIGHTS
6601-01	1/4 x 20	0.08 lb (0.04 kg)
6601-02	3/8 x 16	0.08 lb (0.04 kg)
6601-03	M8	0.15 lb (0.07 kg)
6601-04	M12	0.15 lb (0.07 kg)
5187-00	5/8 x 11	0.05 lb (0.02 kg)
6602-01	3/8 x 16	1.25 lb (0.57 kg)
6602-02	M12	1.25 lb (0.57 kg)
6602-03 (not shown)	M8	1.25 lb (0.57 kg)

Contact your local SECO dealer today!